

Tabela Técnica – Contra Recuo BPG

| Modelo | Torque Nominal [N.m] | RPM | | A [inc] | Chaveta [inc] | B [inc] | C [inc] | D [inc] | E [inc] | F [inc] | *Z [inc] | ROSCAS [inc] |
|---------|----------------------|------|------|---------|---------------|---------|---------|---------|---------|---------|----------|--------------|
| | | Cubo | Capa | | | | | | | | | |
| BPG 300 | 380 | 1300 | 2500 | 0,500" | 1/8" x 1/16" | 3" | 2 5/8" | 2 3/8" | 2 1/2" | 1/2" | 4" | 1/4" -28 |
| | | | | 0,625" | 3/16" x 3/32" | | | | | | | |
| | | | | 0,750" | | | | | | | | |
| BPG 400 | 550 | 1000 | 2400 | 0,625" | 3/16" x 3/32" | 3 1/2" | 2 7/8" | 2 5/8" | 2 3/4" | 5/8" | 4" | 5/16" - 24 |
| | | | | 0,750" | | | | | | | | |
| | | | | 0,875" | | | | | | | | |
| BPG 500 | 1620 | 750 | 2100 | 0,875" | 3/16" x 3/32" | 4 1/4" | 3 5/8" | 3 3/8" | 3 1/2" | 5/8" | 4" | 5/16" - 24 |
| | | | | 1,000" | 1/4" X 1/8" | | | | | | | |
| | | | | 1,125" | | | | | | | | |
| | | | | 1,250" | | | | | | | | |
| | | | | 1,3125" | | | | | | | | |
| BPG 600 | 3100 | 690 | 2000 | 1,250" | 1/4" X 1/8" | 5 3/8" | 4 3/4" | 3 5/8" | 3 3/4" | 5/8" | 6" | 5/16" - 24 |
| | | | | 1,375" | 5/16" X 5/32" | | | | | | | |
| | | | | 1500" | 3/8" x 3/16" | | | | | | | |
| | | | | 1,625" | | | | | | | | |
| | | | | 1,750" | | | | | | | | |
| | | | | 1,9375" | 1/2" x 3/16" | | | | | | | |
| | | | | 2,000" | | | | | | | | |
| BPG 700 | 6900 | 490 | 1500 | 2,000" | 1/2" x 1/4" | 7 1/8" | 6 1/4" | 4 7/8" | 5" | 3/4" | *8" | 3/8" -24 |
| | | | | 2,250" | | | | | | | | |
| | | | | 2,4375" | 5/8" x 5/16" | | | | | | | |
| | | | | 2,500" | | | | | | | | |
| | | | | 2,750" | | | | | | | | |
| | | | | 2,9375" | 5/8" x 1/8" | | | | | | | |
| BPG 750 | 9600 | 310 | 1300 | 2,4375" | 5/8" x 5/16" | 8 3/4" | 7" | 5 7/8" | 6" | 1" | *8" | 1/2" -20 |
| | | | | 2,500" | | | | | | | | |
| | | | | 2,750" | | | | | | | | |
| | | | | 2,9375" | 3/4" X 3/8" | | | | | | | |
| | | | | 3,000" | | | | | | | | |
| | | | | 3,250" | 3/4" X 1/4" | | | | | | | |
| | | | | 3,4375" | 3/4" X 3/16" | | | | | | | |

| | | | | | | | | | | | | |
|-------------|-------|-----|------|---------|----------------|-----|-------------|--------|--------|--------|-----|----------|
| BPG 800 | 17500 | 280 | 1000 | 3,000" | 3/4" X 3/8" | 10" | 8 15/16" | 5 7/8" | 6" | 1" | 8" | 1/2" -20 |
| | | | | 3,250" | | | | | | | | |
| | | | | 3,4375" | 7/8" X 7/16" | | | | | | | |
| | | | | 3,500" | | | | | | | | |
| | | | | 3,750" | | | | | | | | |
| | | | | 3,9375" | 1" X 1/2" | | | | | | | |
| | | | | 4,000" | | | | | | | | |
| | | | | 4,250" | 1" X 3/8" | | | | | | | |
| | | | | 4,4375" | 1" X 1/4" | | | | | | | |
| BPG 900 | 1750 | 220 | 800 | 4,000" | 1" X 1/2" | 12" | 9 3/4" | 6 1/4" | 6 3/8" | 1 1/4" | 10" | 5/8" -18 |
| | | | | 4,250" | | | | | | | | |
| | | | | 4,4375" | | | | | | | | |
| | | | | 4,500" | | | | | | | | |
| | | | | 4,750" | | | | | | | | |
| | | | | 4,9375" | 1" X 3/8" | | | | | | | |
| | | | | 5,000" | | | | | | | | |
| | | | | 5,250" | 1" X 1/4" | | | | | | | |
| | | | | 5,4375" | | | | | | | | |
| BPG 1000 | 34500 | 200 | 700 | 5,000" | 1 1/4" X 5/8" | 15" | 11 3/4" | 6 3/4" | 7" | 1 1/4" | 12" | 5/8" -18 |
| | | | | 5,250" | | | | | | | | |
| | | | | 5,4375" | | | | | | | | |
| | | | | 5,500" | | | | | | | | |
| | | | | 5,750" | 1 1/4" X 7/16" | | | | | | | |
| | | | | 5,9375" | | | | | | | | |
| | | | | 6,000" | | | | | | | | |
| | | | | 6,250" | 1 1/4" X 3/8" | | | | | | | |
| | | | | 6,4375" | | | | | | | | |

*BPG 700 e 750 – Possuem 6 furos equidistantes e 2 furos espaçados a 180° centrados entre os primeiros.

Furos equidistantes ou de acordo com a peça do cliente.